

Laborprüfung Laboratory testing Zertifizierung Certification



eco-INSTITUT-Label

Test criteria: Hard surface cleaners

(Status: May 2021)

A Basic requirements

- Full declaration of materials
- Minimisation requirements for substances with dangerous properties according to dangerous substances regulations.
- Compliance with requirements for harmful substances (refer to C laboratory examinations)
- Compliance with the provisions of the European (e.g. REACH Regulation (EC) No. 1907/2006 and Biocidal products Regulation (EU) 528/2012) and German chemicals legislation
- Materials with the following classifications must not be used in the product:

Phthalatic acid esters, Terephthalatic acid esters (apart from PET), DINCH

Substances excluded according to DE-UZ 194

Substances according to Regulation (EC) No. 1272/2008 Category Carc. 1A and 1B, Muta. 1A and 1B, Repr. 1A and 1B
Substances according to national law (TRGS 905): Category K1A and K1B, M1A and M1B, R1A and R1B
Substances according to MAK lists III1 and III2
Substances according to IARC groups 1 and 2A
Substances requiring official approval as per Appendix XIV of the REACH regulations
Substances of very high concern according to REACH Regulation (EC) No. 1907/2006, Article 59, paragraph 1 (SVHC, Candidate List)
POPs (Persistent Organic Pollutants) according to Regulation (EC) No 850/2004
Arsenic, lead, cadmium, mercury and compounds
Organic compounds of tin
Antimony trioxide
HFC
Organophosphates
Organic halogenated compounds
Pyrethroids

Substances with the following classification (H-phrase) must not be used in the product¹:

Description		H-Statement
Fatal	Fatal if swallowed.	H300
	Fatal in contact with skin.	H310
	Fatal if inhaled.	H330
	May be fatal if swallowed and enters airways.	H304
	Toxic if swallowed.	H301
Toyic	Toxic in contact with skin.	H311
Toxic	Toxic if inhaled.	H331
	Toxic in contact with eyes.	EUH070
	Cause damage to organs.	H370
Specific target organ	May cause damage to organs.	H371
toxicity	Causes damage to organs through prolonged or repeated exposure.	H372
	May cause damage to organs through prolonged or repeated exposure.	H373
Sensitization of	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	H334
respiratory tract	May cause allergic skin reactions.	H317
Carcinogonicity	May cause cancer.	H350
Carcinogenicity	Suspected of causing cancer.	H351
Mutagenicity	May cause genetic defects.	H340
	Suspected of causing genetic defects.	H341
	May damage fertility or the unborn child.	H360
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	H361
	May cause harm to breast-fed children.	H362
Acute hazardous to water	Very toxic to aquatic life.	H400
Charaitae III. haaradaaa	Very toxic to aquatic life with long lasting effects.	H410
Chronically hazardous to water	Toxic to aquatic life with long lasting effects.	H411 (> 1 %)
Hazardous to ozone layer	Hazardous to the ozone layer.	EUH 059

Substances of the following groups of chemicals are exempted from the exclusion of chemicals with certain classifications:

Group of chemical	Classification (H-statement)
Surfactants	H400: Very toxic to aquatic life.
Suractains	H412: Harmful to aquatic life with long-lasting effects.
	H317: May cause an allergic skin reaction.
Enzymes including stabilizers	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

¹ For homogeneous substance mixtures, all input substances > 0.1 % (except for H411) are evaluated. For articles, the overall classification of the input substance or substance mixture (e.g. adhesive, varnish, etc.) is evaluated.

Inputs that have critical hazard characteristics (H-phrase) due to respirable wood dusts or mineral dusts are allowed, provided the overall product does not have a critical hazard characteristic.

Input materials with critical hazard characteristics (H-phrase) for which a requirement value is defined in the laboratory test are permissible, provided that the requirement for emission behavior or content is met.

eco-INSTITUT-Label Test criteria: Hard surface cleaners (Status: May 2021) Page 3 of 5

B Special requirements

- Proportion of renewable carbon in the total carbon of the surfactant system: > 50 %
- Proof of sustainable cultivation of oil plants on certified plantations, if raw materials produced from palm oil and palm kernel oil are used
- Biodegradability of surfactants (readily biodegradable under aerobic conditions and biodegradable under anaerobic conditions) according to DE-UZ 194
- Biodegradability of organic substances according to DE-UZ 194: Content of aerobically not readily biodegradable organic substances < 0.200 g/L cleaning solution; anaerobically non-biodegradable organic substances < 0.500 g/L cleaning solution
- Toxicity to aquatic organisms according to DE-UZ 194: Critical dilution volume toxicity ≤ 18,000 L/L cleaning solution
- Exclusion of biocides according to Biocides Regulation EU No. 528/2012
- Packaging: no use of PVC; weight utility ratio: ≤ 1.2 g/L cleaning solution

C Laboratory examinations

Hard	surface	cleaners
------	---------	----------

Tidio Surface Ciculicis				
Test parameter	Requirement	Test method		
Emission test (4 and 24 hours after test chamber loading)				
TVOC (total volatile organic compounds)	≤ 300 µg/m³			
VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EC) No. 1272/2008: Category Carc. 1A and 1B, Muta. 1A and 1B, Repr. 1A and 1B; TRGS 905: K1A, K1B, M1A, M1B, R1A, R1B; IARC: Group 1 and 2A; DFG (MAK list): Categories III1, III2	≤ 1 µg/m³			
VOC (sum) without NIK	≤ 100 µg/m³			
VOC (individual values):				
Sum of bicyclic terpenes	≤ 200 µg/m³			
Sum of sensitising materials with the following categorisations: DFG (MAK lists): Category IV, TRGS 907	≤ 100 µg/m³			
Sum of VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EC) No. 1272/2008: Category Carc. 2, Muta. 2, Repr. 2; TRGS 905: K2, M2, R2; IARC: Group 2B; DFG (MAK list): Category III3	≤ 50 µg/m³	DIN EN 16516 DIN ISO 16000-6, DIN EN ISO 16000-9 Test chamber conditions:		
Sum C9 – C14 Alkanes / Isoalkanes	≤ 200 µg/m³	cf. testing manual		
Sum C4 – C11 Aldehydes, acyclic, aliphatic	≤ 100 µg/m³	Sample preparation: application of cleaning		
Sum C6 – C15 Alkyl benzenes	≤ 100 µg/m³	solution on glass according		
Sum Cresols	≤ 5 µg/m³	to manufacturer's dosage instructions, minimum: 30		
Sum Xylenes	≤ 100 µg/m³	g/m²		
VOC (individual substances):				
Styrene	≤ 10 µg/m³			
Methylisothiazolinone (MIT)	≤ 1 µg/m³			
Benzaldehyde	≤ 20 µg/m³			
2-Ethyl-1-hexanol, Ethylene glycol mono-butyl ether, 2-Hexoxyethanol, Methyl-isobutylketone (requirements per single substance)	≤ 100 µg/m³			
2-Butoxyethylacetate	≤ 200 µg/m³			
Glycol ethers with insufficient data (requirements per single substance)	0.005 ppm			
Propane-1,2-diol	≤ 60 µg/m³			
2-Phenoxyethanol	≤ 30 µg/m³			
Phenol	≤ 20 µg/m³			
Benzothiazol ²	≤ 15 µg/m³			
Ethylacetat (VVOC)	≤ 600 µg/m³			
TSVOC (total semi-volatile organic compounds)	≤ 100 μg/m³			
R-value	≤ 1.0			
Formaldehyde	≤ 24 μg/m³	DIN EN 16516		

 $^{^{\}rm 2}$ Preliminary, exceeding the limit does not lead to devaluation at present

Hard surface cleaners				
Test parameter	Requirement	Test method		
Emission test (4 and 24 hours after test chamber loading)				
Acetaldehyde	≤ 24 µg/m³	DIN ISO 16000-3		
Odour	\leq Grade 4 (4h after test chamber loading) \leq Grade 3 (24h after test chamber loading at the latest)	cf. testing manual		

Hard surface cleaners			
Test parameter	Requirement	Test method	
Content analysis ³			
AOX (adsorbable organic halogenated compounds)	≤ 1.0 mg/kg	DIN EN ISO 9562	
EOX (extractable organic halogenated compounds)	≤ 2.0 mg/kg	following DIN 38414-S17	
Phthalates (sum) DMP, DEP, DPP, DBP, BBP, DEHP, DNOP, DIBP, BMEP, DHP, DNPP, DIPP, PIPP, DINP, DIDP, DHPD, DHNUP	≤ 100 mg/kg	following DIN EN 15777	
Terephthalate DEHT	≤ 100 mg/kg	following DIN EN 15777	
Diisononyl cyclohexane-1,2-dicarboxylate, DINCH	≤ 100 mg/kg	following DIN EN 15777	
Organotin compounds (requirement per single substance) TBT, DBT, TEBT, MBT, MOT, DOT, TCyT, TPhT	≤ 0.05 mg/kg	Extraction, analysis following DIN EN ISO 17353	
Heavy metals			
Arsenic (As)	≤ 5.0 mg/kg	DIN EN 17294-2	
Cadmium (Cd)	\leq 0.5 mg/kg	(01/2017)	
Chrome total (Cr)	\leq 20.0 mg/kg	DIN EN 16711-1	
Mercury (Hg)	\leq 0.2 mg/kg	(04/2014)	
Nickel (Ni)	≤ 20.0 mg/kg		
Lead (Pb)	≤ 20.0 mg/kg		
Antimony (Sb)	≤ 0.2 mg/kg		
Tin (Sn)	\leq 5.0 mg/kg		
Phosphorous (with reference to the cleaning solution)	≤ 0.02 g/kg		
Amines (azo dyes; only dyed cleaners)	\leq 20 mg/kg	LFBG §64, 82.02-2,-4	
Allergenic dyes materials (dispersion dyes materials; only dyed cleaners)	≤ 50 mg/kg	DIN 54231	
Isothiazolinones (requirements per single substance) BIT, CIT, MIT	≤ 0.1 mg/kg (CIT) ≤ 10 mg/kg (BIT, MIT)	Extraction, HPLC-MS/MS	
pH-value	< 11	DIN EN ISO 3071	
Alkylphenol(ethoxylates)	≤ 20.0 mg/kg	HPLC-MS/MS, GC/MSD	

³ If there are indications that the basic requirements (exclusion of the substance groups listed there) are not met or if there is insufficient information on the substances used, additional ingredient analyses may be necessary.